Yuasa Technical Data Sheet

Yuasa ENL100-12FT Industrial VRLA Battery



Specifications	
Nominal voltage (V)	12
10-hr rate Capacity to 10.8V at 20°C (Ah)	102
Dimensions	
Length (mm)	558 (±2)
Width (mm)	125 (±0.5)
Height (mm)	235 (±1)
Mass (kg)	41
Terminal Type	
Threaded terminal - (M=Male or F=Female)	M6 (M)
Torque (Nm)	6 (±0.5)
Operating Temperature Range	
Storage (in fully charged condition)	-20°C to +50°C
Charge	-15°C to +50°C
Discharge	-20°C to +60°C
Storage	
Capacity loss per month at 20°C (% approx.)	3
Case Material	
Standard	ABS (UL94:V0)
Charge Voltage	
Float charge voltage at 20°C (V)/Block	6.78 (±1%)
Float charge voltage at 20°C (V)/Cell	2.26 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	7.2 (±2%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.40 (±2%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4
Charge Current	
Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	25
Maximum Discharge Current	
1 second (A)	500
1 minute (A)	200
Short-Circuit Current & Internal Resistance	
Internal resistance - according to EN IEC 60896-21 (mΩ)	7.42
Short-Circuit current - according to EN IEC 60896-21 (A)	1905
Impedance	
Measured at 1 kHz (mΩ)	7.5
Design Life & Approvals	
EUROBAT Classification: Long life	12+
Yuasa design life at 20°C (yrs)	15

3rd Party Cerfifications
ISO9001 - Quality Management Systems
ISO14001 - Environmental Management Systems
EN 18001 OHSAS Management Systems
UNDERWRITERS LABORATORIES Inc.

Cert. No.: FM 10626
Cert. No.: EMS 55229

Safety

Installation
Can be installed and operated in any orientation except permanently inverted.

Handles
Batteries must not be suspended by their handles (where fitted).

Vent valves
Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release
VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling
YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

Data Sheet generated on 22/02/2016 – E&OE