SAFETY JOGGER
INDUSTRIAL



PROFLEX 12PACK 2131A

PROFLEX12P

Safety Work Gloves 12PACK

Safety Jogger PROFLEX work gloves provide high-level protection and comfort in tough industries and environments. Features include durability, comfort, and resistance to wear and tear.

Liner	13 Gauge Polyester/Elastane/Latex
Coating	Latex Crinkle Coated
Category	SIF-Silicone Free
Size range	EU 6-12
Sample weight	0.029 kg
Norms	ANSI/ISEA 105:2016 : A1 3 3 EN ISO 21420:2020 EN 388:2016 : 2 1 3 1 A

CE | ANSI /ISEA | 13G | SILICONE FREE

EN ISO 21420



EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Extraordinary grip

You'll have a firm hold on objects whether they are dry, wet, or oily, thanks to the exceptional grip these gloves provide.



BLK

Performance level

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (Coup test)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (TDM 100 test)	2	5	10	15	22	30

a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
c. Tear resistance: based on the amount of force required to tear the sample.
d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.