DATASHEET

JAPCELL®


AAA / LR03
STANDARD




SPECIFICATIONS

Classification:	Alkaline
Chemical System:	Zinc-Manganese Dioxide (Zn/MnO2) No added mercury or cadmium
Designation:	ANSI-15A, IEC-LR6
Nominal Voltage:	1.5 volts
Operating Temp:	-18°C to 55°C (0°F to 130°F)
Typical Weight:	24.0 grams
Typical Volume:	8.1 cubic centimeters
Shelf Life:	5 years at 21°C
Terminal:	Flat Contact

INDUSTRY STANDARD DIMENSIONS (MM)



Continue discharge to 0.8 volts at 20± 2°C



Industry Standard Tests (21°C)					
Application	Load	Daliy period	End voltage (V)	Unit	Normal
Portable lighting	5.1Ω	4m/h,8h/d	0.9	min	228
Remote control	24Ω	15s/m,8h/d	1.0	hour	19.8
Toy	5.1Ω	1h/d	0.8	min	238
Digital audio	50mA	1h/12h,24h/d	0.9	hour	20.4
Photo flash	600mA	10s/m,1h/d	0.9	pulse	297
*	100mA	24h/d	0.9	hour	9.21
Compliant to: IEC 60086, Non-dangerous goods regulation and EU directive 2006/66/EC					

Important Notice: This datasheet contains typical information specific to products manufactured at the time of its publication.

JAPCELL®
Spettrupvej 1A • 8722 Hedensted • Denmark
sales@lakuda.dk • VAT: 25628829 • Phone: +45 76407010 • www.lakuda.dk