CMS 8000 VET MULTIPARAMETER PATIENT MONITOR



Product Code	80700
Unit of sale	1 pc
Minimum order	1
Type	No medical device
Class	

UK-REP	Not required
CH-REP	Not required
EAN/UPC	8023279807004

Description

CMS 8000 VET PATIENT MONITOR ECG, RESP , SpO2, PR, NIBP, TEMP

- 12.1" TFT colour LCD display
- multilingual interface (GB, IT, FR, DE, ES, PT , NL, PL , CZ, TR , RO , RU)
- 8 channel waveform synchronous display
- 7 lead ECG waveform on one screen
- anti-motion, anti-ambient light interference digital SpO2 technology
- AC/DC rechargeable lithium battery
- manual/AUTO/continuous NIBP measurement mode
- standard/OXY- graph/Trend-graph/big characters and view bed interfaces

Technical Specifications

ECG
5-lead, dual channel, 3-lead, single channel
Scan speed: 12.5, 25, 50 mm/s
ST segment monitoring
Measurement and alarm range: -2.0 mV ±2.0 mV

RESP
Method: R-F (RA-LL) impedance
Measurement and alarm range: 0-150 rpm
Apnea alarm: 10-40 sec

NIBP - Oscillometric method
Mode: manual/AUTO/continuous
Measurement interval in AUTO mode:
1/2/3/4/5/10/15/30/60/90/120/240/480/960 min
Measurement period in CONT mode: 5 min
Measurement alarm: 10-270 mmHg

SpO2
Measurement and alarm range: 0-100%
Measurement accuracy: 70-100% ±2%

PR
Measurement and alarm range: 25-250 bpm

TEMP
Measurement and alarm range: 0-50 °C

DEVICE
Power supply: 100-240 V - 50/60 Hz

Safety classification: Classe I type CF
Defibrillation-proof applied part

Standard accessories

- Vet SpO2 probe - 3 m
- 5 leads ECG cable with metal clamps
- NIBP cuff 6-11 cm and extension tube
- Power supply cable
- Temperature probe - rectal
- Manual: GB, IT
- Rechargeable lithium battery