SAFETY JOGGER
PROFESSIONAL



Light

ALIZA OB

Vegan ESD Sandal Lycra

ALIZA sandals offer ESD protection, elastic fit, orthopedic insole support, and slip-resistant comfort. Perfect for medical, catering, and food industries.

Upper	Lorica
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Phylon/Rubber (NBR)
Category	OB / SR, HRO, A, E, ESD
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.250 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



WHT



FUC



LBL



LMG



Stretchable upper
Super elastic and stretchable textile for improved comfort and fit.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	**Lorica**			
	Upper: permeability to water vapor	mg/cm^2/h	1.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	17.8	≥ 15
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	mg/cm^2/h	86.31	≥ 2
	Lining: water vapor coefficient	mg/cm^2	691	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm^3	136	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.42	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.42	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.33	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.35	≥ 0.22
	Antistatic value	MegaOhm	32.7	0.1 - 1000
	ESD value	MegaOhm	51	0.1 - 100
	Heel energy absorption	J	27	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.