SAFETY JOGGER
INDUSTRIAL



Light

# GUSTO S2

**Hygienic Safety Shoes For The Food Industry**

GUSTO offers style, antistatic protection, water and oil resistance and all-day comfort. Perfect for food, beverage and catering professionals.

| | |
|---|---|
| Upper | Nappa Action Leather |
| Lining | Recycled Mesh (100% recycled) |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Midsole | N/A |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S2 / SR, FO, CI |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0<br>JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.570 kg |
| Norms | EN ISO 20345:2022+A1:2024<br>ASTM F2413:2024 |



013



WHT



**Steel toecap**
Robust metal support to protect the feet of the wearer against falling or rolling objects.




**SRC slip resistance**
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Water resistant Upper (WRU)**
Prevents penetration of water if not permanently exposed to high levels.



**Oil & fuel resistant**
The outsole is resistant against oil and fuel.



**Heel energy absorption**
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



**Antistatic**
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

## Industries:
Catering, Cleaning, Construction, Food & beverages, Medical, Industry

## Environments:
Dry environment, Wet environment

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---|---|---|---|---|
| **Upper** | **Nappa Action Leather** | | | |
| | Upper: permeability to water vapor | mg/$cm^2$/h | 2.66 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/$cm^2$ | 24 | ≥ 15 |
| **Lining** | **Recycled Mesh (100% recycled)** | | | |
| | Lining: permeability to water vapor | mg/$cm^2$/h | 86.31 | ≥ 2 |
| | Lining: water vapor coefficient | mg/$cm^2$ | 691 | ≥ 20 |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| **Outsole** | **PU/PU** | | | |
| | Outsole abrasion resistance (volume loss) | $mm^3$ | 32 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.41 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.38 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.27 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.26 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 330.1 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 25 | ≥ 20 |
| **Toecap** | **Steel** | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 19.5 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.