SAFETY JOGGER
INDUSTRIAL



Medium

FLUX S3S LOW TLS

FLUXS3SLTL

Lightweight comfortable and metal-free S3S low-cut with TLS closing


The FLUX S3S LOW TLS is a low-cut safety shoe with a synthetic nubuck upper for water resistance and durability. Features a nanocarbon toecap, metal-free puncture-resistant midsole, and PU cleated outsole for strong grip on dry, wet, and slippery surfaces. Equipped with a TLS-closure system for easy and quick adjustment.

Upper	TPU, Synthetic Nubuck
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)
Midsole	Anti-Puncture Textile
Outsole	PU/PU
Toecap	Nano Carbon
Category	S3S / SR, SC, FO, CI, ESD
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.546 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK





Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



TLS (Twist Lock System)
Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



Scuff Cap (SC)
Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Nano carbon toecap
Ultralight high-tech material, metalfree with no thermal or electrical conductivity.

Industries:
Automotive, Industry, Assembly, Logistics, Food & beverages, Cleaning, Catering

Environments:
Dry environment, Extreme slippery surfaces, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	**TPU, Synthetic Nubuck**			
	Upper: permeability to water vapor	mg/cm^2/h	2.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	19.9	≥ 15
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	mg/cm^2/h	49.8	≥ 2
	Lining: water vapor coefficient	mg/cm^2	398.8	≥ 20
Footbed	**SJ Recycled Memory Foam Footbed (90% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	mm^3	40.9	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.49	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.48	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.30	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.25	≥ 0.22
	Antistatic value	MegaOhm	18.7	0.1 - 1000
	ESD value	MegaOhm	5.2	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	**Nano Carbon**			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.