SAFETY JOGGER TACTICAL



Medium

# MODULO DELTA 06 LOW

MDLODLTLOW

**Waterproof Low Occupational Shoes**

MODULO DELTA 06 LOW waterproof leather shoes give workers secure grip, slip & heat resistance, and lasting protection indoors and outdoors.

| | |
|---|---|
| Upper | Milled Full-Grain Leather |
| Lining | Membrane, Recycled 3D-Mesh (100% recycled) |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Outsole | BASF PU/Rubber (NBR) |
| Category | 06 / SR, SC, LG, FO, HI, HRO, CI, ESD |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5<br>JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.555 kg |
| Norms | EN ISO 20347:2022+A1:2024<br>ASTM F2892:2024 |




BLK



**Breathable leather upper**
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



**Heat resistant outsole (HRO)**
The outsole resists high temperatures up to 300°C.




**Metal free**
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



**Waterproof (WR)**
Waterproof footwear prevents liquids to enter into the shoe.



**Electrostatic Discharge (ESD)**
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



**Heel energy absorption**
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

## Industries:
Tactical, Uniform

## Environments:
Extreme slippery surfaces, Wet environment

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---|---|---|---|---|
| **Upper** | **Milled Full-Grain Leather** | | | |
| | Upper: permeability to water vapor | mg/$cm^2$/h | 2.71 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/$cm^2$ | 26 | ≥ 15 |
| **Lining** | **Membrane, Recycled 3D-Mesh (100% recycled)** | | | |
| | Lining: permeability to water vapor | mg/$cm^2$/h | 6.36 | ≥ 2 |
| | Lining: water vapor coefficient | mg/$cm^2$ | 51 | ≥ 20 |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | Dry 25600 cycles/Wet 12800 cycles | 25600/12800 |
| **Outsole** | **BASF PU/Rubber (NBR)** | | | |
| | Outsole abrasion resistance (volume loss) | $mm^3$ | 117 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.44 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.42 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.29 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.32 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 28.4 | 0.1 - 1000 |
| | ESD value | MegaOhm | 33 | 0.1 - 100 |
| | Heel energy absorption | J | 35 | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.