SAFETY JOGGER TACTICAL



Medium

MODULO DELTA 06 MID

MDLODLTMID

Waterproof Mid Occupational Shoe

MODULO DELTA 06 MID waterproof leather shoes give workers secure grip, slip & heat resistance, and lasting protection indoors and outdoors.

Upper	Milled Full-Grain Leather
Lining	Recycled 3D-Mesh (100% recycled), Membrane
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	BASF PU/Rubber (NBR)
Category	06 / SR, SC, LG, FO, HI, HRO, CI, ESD
Size range	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
Sample weight	0.603 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024





BLK




Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Waterproof (WR)
Waterproof footwear prevents liquids to enter into the shoe.

Industries:
Tactical, Uniform

Environments:
Extreme slippery surfaces, Wet environment

	Description	Measure unit	Result	EN ISO 20347
Upper	**Milled Full-Grain Leather**			
	Upper: permeability to water vapor	mg/cm^2/h	2.71	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	26	≥ 15
Lining	**Recycled 3D-Mesh (100% recycled), Membrane**			
	Lining: permeability to water vapor	mg/cm^2/h	6.36	≥ 2
	Lining: water vapor coefficient	mg/cm^2	51	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	**BASF PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm^3	117	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.42	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	28.4	0.1 - 1000
	ESD value	MegaOhm	33	0.1 - 100
	Heel energy absorption	J	35	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.