SAFETY JOGGER
INDUSTRIAL



Light

# GOBI S1 P

**Lightweight Safety Shoes With S1P Protection**

GOBI steel toe safety shoes with puncture-resistant midsole guards against hazards, while its slip resistant grip ensures footing and breathable comfort.

| | |
|---|---|
| Upper | Suede Leather |
| Lining | Recycled Mesh (100% recycled) |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Midsole | Steel |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S1 P / SRC |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0<br>JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.670 kg |
| Norms | ASTM F2413:2018<br>EN ISO 20345:2011 |



BLK



NAV




**S1P**
You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



**Steel toecap**
Robust metal support to protect the feet of the wearer against falling or rolling objects.



**Steel midsole**
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.




**SRC slip resistance**
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Antistatic**
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



**Heel energy absorption**
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

## Industries:
Automotive, Construction, Logistics, Industry

## Environments:
Dry environment

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---|---|---|---|---|
| **Upper** | **Suede Leather** | | | |
| | Upper: permeability to water vapor | mg/$cm^2$/h | 11.7 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/$cm^2$ | 101.6 | ≥ 15 |
| **Lining** | **Recycled Mesh (100% recycled)** | | | |
| | Lining: permeability to water vapor | mg/$cm^2$/h | 67.6 | ≥ 2 |
| | Lining: water vapor coefficient | mg/$cm^2$ | 541 | ≥ 20 |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| **Outsole** | **PU/PU** | | | |
| | Outsole abrasion resistance (volume loss) | $mm^3$ | 127 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.30 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.32 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 16.3 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 27 | ≥ 20 |
| **Toecap** | **Steel** | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 17.0 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.