SAFETY JOGGER
INDUSTRIAL



Medium

BESTRUN2 S3

All features of the original Bestrun in an updated design


Safety Jogger BESTRUN2 combines SR slip resistance, steel toecap, orthopedic comfort and a breathable leather upper for all work environments.

Upper	Barton Action Leather
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, SC, FO, CI
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.625 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



217

DGUV BGR 191
These shoes are suitable for orthopedic insoles and orthopedic alterations. Certified according to BGR 191.



SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:
Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Oil & Gas, Industry

Environments:
Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	**Barton Action Leather**			
	Upper: permeability to water vapor	mg/cm^2/h	2.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	25.0	≥ 15
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	mg/cm^2/h	49.8	≥ 2
	Lining: water vapor coefficient	mg/cm^2	398.8	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	mm^3	35.6	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.43	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.24	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.26	≥ 0.22
	Antistatic value	MegaOhm	55.1	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	23	≥ 20
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	23.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.