

SAFETY JOGGER PROFESSIONAL

Light

DOMINIQUE 01

Stylish Sneakers with Advanced Shock Absorption Technology

DOMINIQUE is a trendy, shock-absorbing sneaker with air cushioning, slip-resistant grip, and breathable comfort for everyday performance.

Upper	Action Leather, Textile
Lining	Recycled 3D-Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	PU/Rubber (NBR)
Category	01 / SR, FO, HRO, ESD
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.400 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BLK



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Extreme slippery surfaces, Uneven surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	**Action Leather, Textile**			
	Upper: permeability to water vapor	mg/cm^2/h	21.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	21.6	≥ 15
Lining	**Recycled 3D-Mesh (100% recycled)**			
	Lining: permeability to water vapor	mg/cm^2/h	42.7	≥ 2
	Lining: water vapor coefficient	mg/cm^2	342.3	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm^3	81	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.38	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.39	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	97.4	0.1 - 1000
	ESD value	MegaOhm	73.6	0.1 - 100
	Heel energy absorption	J	37	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.