SAFETY JOGGER
PROFESSIONAL



Light

# HENNY OB

**Men's Fashionable Sneakers**

HENNY work shoes combine grip, support, and breathable comfort for safe performance in food, cleaning, and medical industries.

| | |
|---|---|
| Upper | Action Leather |
| Lining | Recycled Mesh (100% recycled) |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Outsole | TPR |
| Category | OB / E |
| Size range | EU 36-47 / UK 3.5-12.0 / US 4.0-13.0<br>JPN 22.5-31 / KOR 235-310 |
| Sample weight | 0.420 kg |
| Norms | EN ISO 20347:2022(Europe) |



LGR



NAV




**Coolmax® lining**
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

## Industries:
Cleaning, Food & beverages, Medical

## Environments:
Dry environment

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---|---|---|---|---|
| **Upper** | **Action Leather** | | | |
| | Upper: permeability to water vapor | mg/$cm^2$/h | 1.1 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/$cm^2$ | 16.8 | ≥ 15 |
| **Lining** | **Recycled Mesh (100% recycled)** | | | |
| | Lining: permeability to water vapor | mg/$cm^2$/h | 51 | ≥ 2 |
| | Lining: water vapor coefficient | mg/$cm^2$ | 408.7 | ≥ 20 |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| **Outsole** | **TPR** | | | |
| | Outsole abrasion resistance (volume loss) | $mm^3$ | 145 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.35 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.39 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | N/A | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | N/A | ≥ 0.22 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 24 | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.