SAFETY JOGGER
PROFESSIONAL



Light

JULINE OB

JULINE2

Stylish Work Pump

The stylish JULINE work pumps offer superior comfort, excellent grip, and body posture relief. Perfect for uniform and catering industries.

Upper	Lorica
Lining	Synthetic Leather
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Rubber (NBR)
Category	OB / SR, FO, HRO, E
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.270 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F3445:2024




BLK



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.




SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.




Breathable upper
Increased moisture and temperature management for extended wearer comfort.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Rubber outsole
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Catering, Uniform

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	**Lorica**			
	Upper: permeability to water vapor	mg/cm^2/h	1.8	≥ 0.8
	Upper: water vapor coefficient	mg/cm^2	17.3	≥ 15
Lining	**Synthetic Leather**			
	Lining: permeability to water vapor	mg/cm^2/h	86.31	≥ 2
	Lining: water vapor coefficient	mg/cm^2	691	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	**Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm^3	89	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.36	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.37	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.25	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.28	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	50	≥ 20

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.