MINISPIR - PC SPIROMETER with software



Product Code	33528
Unit of sale	1 pc
Minimum order	1
Type	Medical device
Class	II A

RDM (NSIS)	2621401
CND	Z12150102
EAN/UPC	8023279335286

Description

MINISPIR with MIR SPIRO PC SOFTWARE

Real time Flow/Volume loop and Volume/time curve with PRE/POST comparison. Advanced spirometry test interpretation. Pediatric incentive animations. Lung Age. Temperature sensor for BTPS conversion. Supplied with reusable turbine.

32 measured parameters: FVC, FEV1,
FEV1%, FEV3, FEV3%, FEV6, FEV1/FEV6%, PEF, FEF25%, FEF50%, FEF75%, FEF25-75%, FET, Vext, Lung Age, FIVC, FIV1, FIV1%, PIF, VC, IVC, IC, ERV, FEV1/VC%, VT, VE, Rf, ti, te, ti/t-tot, VT/ti, MVV. Manual GB, IT (FR, ES, DE, PT, DK, NL, PL,SE, HU, BG, GR available on www.gimaitaly.com). MDR certified.

Made in Italy.

<HR>

MIR SPIRO PC software
The next-generation software for Spirometry and Oximetry.
It complies with ATS/ERS 2019. Powerful and advanced, provides a wide range of features in a new graphic and customizable settings. New user interface, much more user intuitive and easier interoperability for EHR/ EMR integration. Automatic updates provide the latest version of software.

MIR Spiro PC Software one year licence subscription included with all MIR spirometers and oximeter.
MIR Spiro software licence has one-year validity
Annual Platinum subscription renewal on mymir.spirometry.com

TEST:
FVC Pre/Post, SVC Pre/Post
Oximetry Spot
24h oximetry holter
MVV Pre/Post
Oximetry 6MWT, Oximetry Sleep

PATIENT MANAGEMENT:
New patient / Patient List / Patient Search
Patient Session Summary
Patient Risk factors/Symptoms
Test cronology comparison
Worklist

PRINTOUTS:
FVC Printout STD and ATS 2019
FVC Printout STD NIOSH/OSHA
Oximetry Calibration Printout and VC Printout
Quality Grade Printout

DATA MANAGEMENT:
Data sharing/Interoperability

Data import from Legacy db
Data Import from third parties sfw db
Data Export in Excel/csv/ATS/HL7/GDT
Data Recovery
Emphysema Severity Index (ESI)
ESI Method Artificial Intelligence

PC SYSTEM REQUIREMENTS:
Windows: 8, 10, 11 (all 32, 64 bit); RAM 1 GB for 32 bit or 2 GB for 64 bit / 1 GHz or faster processor, two or more cores in a 64 bit processor / 1 GB free hard disk space
Mac iOS: operating system from 10.13; RAM 2 GB (recommended 4 GB) / 1 GB free hard disk space
Connection: USB port or Bluetooth low energy
Multilingual software: GB, FR, IT, ES, PT, DE, PL, HU, RO, SE, NL, CZ, LV, TR, UA, GE, RU, CN, JP

Technical Specifications

Temperature sensor: semiconductor (0-45°C)
Flow sensor: bi-directional digital turbine
Flow range: ± 16 L/s
Volume accuracy: ± 2.5% or 50 mL
Flow accuracy: ± 5% or 200 mL/s
Dynamic resistance at 12 L/s: <0.5 cm H2O/L/s
Communication port: USB
Power Supply: line powered from USB port
Dimension: 50x142x26 mm
Weight: 65 g