SAFETY JOGGER
TACTICAL



Medium

# TACTIC LOW OB

TACTICLOW

**Allround Tactical Shoes Low**

TACTIC LOW is a durable tactical boot built for uneven terrain, offering grip, comfort, and protection in demanding environments.

| | |
|---|---|
| Upper | Textile, Full Grain Leather |
| Lining | Recycled Mesh (100% recycled) |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Outsole | Rubber (NBR) |
| Category | OB / SR, LG, FO, HI, HRO, E, CI |
| Size range | EU 35-48 |
| Sample weight | 0.565 kg |
| Norms | EN ISO 20347:2022+A1:2024<br>ASTM F3445:2024 |



BLK




**SRA slip resistance**
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



**Heat resistant outsole (HRO)**
The outsole resists high temperatures up to 300°C.



**Oil & fuel resistant**
The outsole is resistant against oil and fuel.



**Breathable leather upper**
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

## Industries:
Tactical, Uniform

## Environments:
Uneven surfaces, Muddy environment

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---|---|---|---|---|
| **Upper** | **Textile, Full Grain Leather** | | | |
| | Upper: permeability to water vapor | mg/$cm^2$/h | 4.5 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/$cm^2$ | 35 | ≥ 15 |
| **Lining** | **Recycled Mesh (100% recycled)** | | | |
| | Lining: permeability to water vapor | mg/$cm^2$/h | 45 | ≥ 2 |
| | Lining: water vapor coefficient | mg/$cm^2$ | 350 | ≥ 20 |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| **Outsole** | **Rubber (NBR)** | | | |
| | Outsole abrasion resistance (volume loss) | $mm^3$ | 107 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.40 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.45 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.22 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.25 | ≥ 0.22 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 36 | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.