



SAFETY JOGGER

PROFESSIONAL



Heavy

OXYVA OB

Lightweight Clogs With Unmatched Comfort

OXYVA clogs are lightweight, waterproof, ESD protected, UV and chemical sterilizable. Ideal for medical, cleaning and catering professionals.

Upper	Expanded EVA
Lining	N/A
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Expanded EVA
Category	OB / SR, A, E, ESD
Size range	EU 35-46 / UK 3.0-11.0 / US 3.0-12.0 JPN 21.5-30 / KOR 230-300
Sample weight	0.222 kg
Norms	ASTM F2892:2018 EN ISO 20347:2022(Europe)



EBL



BLK



EGN



FUX



LIC



NAV



WHT



Hygienic waterproof solution

This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.



Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Washable 30°C

These shoes can be washed in a washing machine at 30°C.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.

SAFETY JOGGER
WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:
Medical, Catering, Cleaning, Food & beverages

Environments:
Dry environment, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Expanded EVA			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Lining	N/A			
	Lining: permeability to water vapor	mg/cm ² /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm ²	N/A	≥ 20
Footbed	SJ Recycled Foam Footbed (96% recycled)			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Expanded EVA			
	Outsole abrasion resistance (volume loss)	mm ³	130	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.31	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.36	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.19	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.22	≥ 0.22
	Antistatic value	MegaOhm	29.4	0.1 - 1000
	ESD value	MegaOhm	6.8	0.1 - 100
	Heel energy absorption	J	77	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.